



轴承代号 Bearing No.	内径尺寸 d (mm) Bore Dia Of		外形尺寸 (in) Dimensions (mm)									额定动负荷 Basic Load Rating CR(KN)	额定静负荷 Basic Static Load Rating COR(KN)	重量 Weight (KG)
	(in)	(mm)	D	B	B1	C	S	B3	d1	h	ds			
NA 205-14 205-15 205 205-16	7/8 15/16	25	2.0472 52	1.3701 34.8	1.7441 44.3	0.6693 17	0.6850 17.4	0.5315 13.5	1.5000 38.1	0.1772 4.5	M6x1 1/4-28	14.03	7.06	0.290 0.270 0.250 0.249
NA 206-17 206-18 206 206-19 206-20	1 1/16 1/8 1 3/16 1 1/4	30	2.4409 62	1.4331 36.4	1.9016 48.3	0.7480 19	0.7165 18.2	0.6260 15.9	1.7520 44.5	0.2087 5.3	M8x1 5/6-28	19.47	11.26	0.450 0.410 0.408 0.380
NA 207-20 207-21 207-22 207 207-23	1 1/4 1 5/16 1 3/8 1 7/16	35	2.8346 72	1.4803 37.6	2.0118 51.1	0.7874 20	0.7402 18.8	0.6890 17.5	2.1890 55.6	0.2244 5.7	M8x1 5/16-24	20.67	15.29	0.680 0.650 0.610 0.608 0.580
NA 208-24 208-25 208	1 1/2 1 9/16	40	3.1496 80	1.6850 42.8	2.2165 56.3	0.8268 21	0.8425 21.4	0.7205 18.3	2.3740 60.3	0.2480 6.3	M8x1 5/16-24	22.71	15.94	0.830 0.800 0.780
NA 209-26 209-27 209-28 209	1 5/8 1 1 1/16 1 3/4	45	3.3465 85	1.6850 42.8	2.2165 56.3	0.8661 22	0.8425 21.4	0.7205 18.3	2.5000 63.5	0.2677 6.8	M8x1 5/16-24	24.36	17.71	0.980 0.910 0.870 0.840
NA 210-30 210-31 210 210-32	1 7/8 1 15/16 2	50	3.5433 90	1.9370 49.2	2.4685 62.7	0.9449 24	0.9685 24.6	0.7205 18.3	2.7520 69.9	0.2638 6.7	M10x1.25 3/8-24	27.50	20.20	1.100 1.040 1.030
NA 211-32 211-34 211 211-35	2 2 1/8 2 3/16 2 1/4	55	3.9370 100	2.1811 55.4	2.8110 71.4	0.9843 25	1.0906 27.7	0.8189 20.8	3.0000 76.2	0.2835 7.2	x1.25 3/8-24	33.40	25.10	1.580 1.440 1.390 1.360
NA 212-36 212 212-38 212-39	2 1/4 2 3/8 2 7/16	60	4.3307 110	2.4331 61.8	3.0591 77.7	1.0630 27	1.2165 30.9	0.8780 22.3	3.3071 84	0.3228 8.2	x1.25 3/8-24	41.00	31.50	2.030 1.870 1.850 1.760
NA 213-40 213	2 1/2	65	4.7244 120	2.6850 68.2	3.3740 85.7	1.1024 28	1.3425 34.1	0.9252 23.5	3.3858 86	0.3150 8.0	x1.25 3/8-20	44.40	34.20	2.510 2.410
NA 214-44 214	2 3/4	70	4.921 125	2.6850 68.2	3.3740 85.7	1.1811 30	1.3425 34.1	0.9409 23.9	3.7795 96	0.3543 9.0	x1.25 3/8-20	46.79	37.59	2.580 2.570
NA 215 215-47 215-48	2 15/16 3	75	5.1181 130	2.9370 74.6	3.6260 92.1	1.1811 30	1.4685 37.3	0.9409 23.9	4.0157 102	0.3543 9.0	x1.25 3/8-20	55.40	41.26	2.840 2.740
NA216		80	5.5118 140	2.9370 74.6	3.7480 95.2	1.2912 33	1.4685 37.3	1.0630 27	4.3307 110	0.4016 10.2	M12x1.25	55.80	44.60	3.18